



Vickers 02-157588

Industrial Valves - Proportional; directional valve; size D03 NG6; servo performance with feedback

Model Code: KSDG4V-3-92L-24-M-U1-H7-11 [Modify Configuration](#)

Compare Favorite

Where to Buy

Contact Me

[+ PRICING & DELIVERY](#)

Product Specifications

Feature	Code	Description
VALVE TYPE	K	(K) PROPORTIONAL VALVE WITHOUT INTEGRAL AMPLIFIER
FEEDBACK ARRANGMENT	S	(S) CLOSED-LOOP
CONTROL TYPE	D	(D) DIRECTIONAL VALVE
MOUNTING	G	(G) SUB PLATE MOUNTED
OPERATION	4	(4) SOLENOID OPERATED
PRESSURE RATING	V	(V) MAX PRESSURE 315 BAR
INTERFACE	-3	(3) ISO-4401 SIZE 03-02-0-94
SPOOL OVERLAP CONDITION	-9	(9) ZERO UNDERLAP
SPOOL TYPE	2	(2) P,A,B,T BLOCKED
VALVE BUILD	L	(L) STANDARD BUILD
RATED FLOW	-24	(24) 24 L/MIN (6.3 USGPM)
FLAG SYMBOL	-M	(M) ELECTRICAL FLAG
ELECTRICAL CONNECTION	-U1	(U1) ISO 4400/DIN 43850
COIL VOLTAGE	-H	(H) 24V DC
TANK PORT RATING	7	(7) 210 BAR
DESIGN CODE	-11	(11) DESIGN NUMBER