

CBD Series

with **UL94V-0 polyamide insulating body**

- UL94V-0
- universal mounting onto both PR/DIN and PR/3 type rails - according to IEC 60715 Std., "G32" and "TH/35" types
- **CESI 01 ATEX 090 U** Ex e certificate I M2 / II 2 G D operating temperature range: -40 ÷ +80 °C
- **CoC IEC Ex CES 09.0009U** Ex e II
- when rail assemblies are to be manufactured for potentially explosive environments (Ex e) please refer to the instructions given on page A14
- available in standard (beige RAL 1001 colour) or (Ex) i "intrinsic safety" circuits (blue RAL 5015 colour)



(* if shielded cables are to be connected when using CB/SH screening lug, the rated voltage is reduced to 250 V

beige version	
(Ex)i version	
TECHNICAL CHARACTERISTICS	
function / type	
rated cross-section	(mm ²)
connecting capacity	
flexible	(mm ²)
rigid	(mm ²)
max. flexible with ferrule (mm ²)-ferrule type	
rated voltage / rated current / gauge	conf. to IEC 60947-7-1
rated voltage / rated current / AWG / tightening torque value	UL (Ex e) rated voltage / (V)
rated impulse withstand voltage / pollution degree	
insulation stripping length	(mm)
tightening torque value (test / max)	(Nm)
height / width / thickness	TH/35 7,5 mm
height / width / thickness	TH/35 15 mm
height / width / thickness	G32

APPROVALS

CBD.10	Cat. No. CB440
CBD.10 (Ex)i	Cat. No. CBX45
feed-through	10
0,5 ÷ 16	
0,5 ÷ 16	
10 - WP100/21	
800 V / 57 A / B6	
600 V / 60 A / 20-6 AWG / 13,3 lb.in	
500 V / 630 V	
8 KV / 3	
14	
1,2 / 1,9	
55 / 44 / 10	
63 / 44 / 10	
59 / 44 / 10	
IEC Ex pending	

CBD.16	Cat. No. CB510
CBD.16 (Ex)i	Cat. No. CBX52
feed-through	16
0,5 ÷ 25	
0,5 ÷ 25	
16 - WP160/22	
800 V / 76 A / B7	
600 V / 100 A / 20-3 AWG / 19,9 lb.in	
630 V / 630 V	
8 KV / 3	
18	
1,8 / 3	
57 / 47 / 12	
65 / 47 / 12	
61 / 47 / 12	
IEC Ex pending	

CBD.35	Cat. No. CB610
CBD.35 (Ex)i	Cat. No. CBX62
feed-through	35
0,5 ÷ 35	
0,5 ÷ 50	
35 - WP350/30	
800 V / 125 A / B8	
600 V / 125 A / 16 ÷ 1 AWG / 22,1 lb.in	
630 V / 630 V	
8 KV / 3	
20	
2 / 3,5	
60 / 52 / 16	
68 / 52 / 16	
64 / 52 / 16	
IEC Ex pending	

ACCESSORIES

End sections	beige blue
Permanent cross connection	
Rated current carrying capacity of jumper (same, Ex e version)	(A)
Switchable cross connection	
Multiple common bar	250 mm
Shunting screw and sleeve (same, Ex e version)	
Coloured partition	red, green, white
Cross connection barrier	red
Test plug socket	
Test plug	
Modular test plug	
End section for modular test plug	
Numbering strip	
Warning plate	on adjacent terminal blocks
Cover for cross-connection	
Marking tag	printed or blank
End bracket	
Mounting rail according to IEC 60715 Std.	
Screening lug	

Type	Cat. No.
CB10/PT	CB431
CB10/PT (Ex)i	CBX44
PM/10/2 poles (pre-assembled)	PM102
PM/10/3 poles (pre-assembled)	PM103
PM/10/5 poles (pre-assembled)	PM105
PM/10/10 poles (pre-assembled)	PM100
57 / (57)	
POS/44	POS44
PMP/04	PMP04
CPM/03 (CPX/03)	CPM03 (CPX03)
DFU/4	DU04..
DFM/700	DF700
PSD/B	PD002
SDD/2	DD002
-	
-	
-	
TTM/04 on 3	TTM04
TQM/04 on 4	TQM04
PRP/7	PRP07
CNU/8/51	NU0851
BTU for PR/DIN and PR/3	BT005
BT/DIN/PO for PR/DIN only	BT001
BT/3-BTO for PR/3 only	BT003-BT007
PR/DIN/AC of steel	PR001
PR/DIN/AS same with slots	PR004
PR/DIN/AL of aluminium	PR002
PR/3/AC of steel	PR003
PR/3/AS same with slots	PR005
CBD/SH (*)	CB009

Type	Cat. No.
CB16/PT	CB511
CB16/PT (Ex)i	CBX53
POF/44 (PFX/44)	POF44 (PFX44)
(same, Ex e version)	
76 / (76)	
POS/44	POS44
PMP/05	PMP05
CPM/44 (CPX/44)	CPM44 (CPX44)
DFU/4	DU04..
DFM/700	DF700
PSD/B	PD002
SDD/2	DD002
-	
-	
-	
TUM/05 on 3 and on 4	TUM05
PRP/7	PRP07
CNU/8/51	NU0851
BTU for PR/DIN and PR/3	BT005
BT/DIN/PO for PR/DIN only	BT001
BT/3-BTO for PR/3 only	BT003-BT007
PR/DIN/AC of steel	PR001
PR/DIN/AS same with slots	PR004
PR/DIN/AL of aluminium	PR002
PR/3/AC of steel	PR003
PR/3/AS same with slots	PR005
-	

Type	Cat. No.
CB35/PT	CB611
CB35/PT (Ex)i	CBX63
POF/06 (PFX/06)	POF06 (PFX06)
(same, Ex e version)	
125 / (125)	
POS/66	POS66
PMP/06	PMP06
CPM/06 (CPX/06)	CPM06 (CPX06)
DFU/5	DU05..
DFM/700	DF700
PSD/B	PD002
SDD/2	DD002
-	
-	
-	
TUM/06 on 3 and on 4	TUM06
PRP/8	PRP08
CNU/8/51	NU0851
BTU for PR/DIN and PR/3	BT005
BT/DIN/PO for PR/DIN only	BT001
BT/3-BTO for PR/3 only	BT003-BT007
PR/DIN/AC of steel	PR001
PR/DIN/AS same with slots	PR004
PR/DIN/AL of aluminium	PR002
PR/3/AC of steel	PR003
PR/3/AS same with slots	PR005
-	